



DRIPSTONE

TELARAN COMMUNICATIONS (1986) LTD
טלראן תקשורת (1986) בע"מ



2021

p.n.560754

Fingerprint Access Control with proxy

Feature

Waterproof, up to IP66
Metal Design & Anti-Vandal
Standalone, one relay
1,000 fingerprint, 2,000 Card users
Card type: EM Card, or Mifare Card, or EM + HID Card
Wiegand 26~44 output
Pulse mode, toggle mode
Multi fingerprints/PINs access
Interlock, Support Principal User



Fax: 03-5214524
office@telran.co.il



Phone: 03-5575110
www.telran.co.il



Specification

User Capacity Fingerprint Card	3000 1000 2000
Card Type:	125KHz EM Card
Operating Voltage Idle Current Active Current	12V DC ≤ 45mA ≤ 150mA
Fingerprint Reader Resolution Identification time	Optical Fingerprint Module 500DPI <1S
FAR / FRR	<0.001% / <0.01%
Wiring Connections	Relay output, exit button, alarm, door contact, Wiegand output
Relay Adjustable Relay Output Time Adjustable Alarm Output Time	One (NO, NC, Common) 0~99 Seconds (5 seconds default) 0~3 Minutes (default: 1 minute)
Lock Output Load Alarm Output Load	2 Amp Maximum 5 Amp Maximum
Wiegand Interface	Wiegand 26~44bits output
Environment Operating Temperature Operating Humidity	Meets IP66 -30°C ~ 60°C (-22°F ~ 140°F)--Default -40°C ~ 60°C (-40°F ~ 140°F)--Optional 20%RH ~ 90%RH
Physical Surface Finish	Zinc-Alloy Powder Coat
Dimensions Unit Weight/Shipping Weight	L135 x W55 x H26 (mm) 400g/500g