



Model Number 08013

24+2 10/100Mbps 400W PoE Switch IEEE802.3af/at

Features:

- 24*10/100Mbps RJ45 PoE ports, 2*10/100/1000Mbps RJ45 uplink ports
- 250m Distance
- Power Built-in
- VLAN Support
- Support IEEE802.3AF/AT
- Whole Power: 400W (52V 7.7A)
- Max. Power for Each port: 30W
- All port supported by MDI/MDIX auto flip and self-negotiation
- Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.
- Application: Wireless Access Point, IP Camera, IP Phone, Computer Networks



[לצפייה באתר לחץ כאן](#)

Application:

- Wireless Access Point
- IP Camera
- IP Phone
- Computer Networks



Specification:

Product	24+2 10/100Mbps 400W PoE Switch IEEE802.3af/at
Model No.	08013
PoE Port	1 to 24 port support IEEE802.3af/at
UP link port	25 th -26 th port support 1000Mbps
PoE output	15.4W/30W IEEE802.3af/at
PoE whole power	≤400W
PoE type	End-span
Power distance	≤250m
Network Standard	IEEE 802.3 、 IEEE802.3u 、 802.3x 、 802.3af/at
Network Medium	100/1000BASE-TX: 5 class and above non shielded twisted pair
Data Distance	≤250m
Switch capability	12Gbps
Forwarding Mode	Store and forward
Forwarding Rate	• 100Mbps:14880pps • 1000Mbps:14800pps • 1000BASE-T: 1488095pps/port
MAC Address	2K MAC address table
Port function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
Indicator	LINK/ACT. 100Mbps;POE Status indicator; POWER indicator EXTENDER indicator
Working Environment	Working Temperature: -10°-- 55°C
Input power	AC100-240V 50/60HZ
Weight	2.5kg
Size	270mm*180mm*44mm (L*W*H)