



Model Number 08011

4+1 Giga 78W PoE Switch IEEE802.3af/at

Features:

- Wireless Access Point
- IP Camera
- IP Phone
- Computer Networks
- 4*100/1000mbps POE port, 1*100/1000mbps UP Link port
- 100m Distance
- Support IEEE802.3AF/AT
- Whole Power: 78W (52V 1.5A)
- All port supported by MDI/MDIX auto flip and self negotiation
- Supply 4 10/100Mbps adaptive high speed forwarding data packet non-lost port.
- Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.
- Each port max. power supply reached 30W



[לצפייה באתר לחץ כאן](#)

Specification:

Item	4+1 Giga 78W PoE Switch IEEE802.3af/at
Model No.	08011
POE Port	1 to 4 support IEEE802.3AF/AT Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	Both 1/2+, 3/6- and 4/5+ 7/8-
Whole Power	≤78W (52V 1.5A)
POE Portocol	IEEE 802.3af/IEEE 802.3at
POE Type	End-span
Power Distance	≤100m
Network Standard	IEEE 802.3, IEEE802.3u, 802.3x, 802.3af/at
Network Medium	10/100BASE-TX: 5 class and above non shielded twisted pair
Data Distance	≤100m
Switch Capability	12Gbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-T: 14880PPS/port 100BASE-tx: 148800pps/port 1000BASE-T: 1488000pps/port
MAC Address	MAC address table 8K

Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	Each port occupied 1 LINK/ACT.100Mbps, POE Status Indicator, Whole power indicator
Working Environment	Working temperature:-10°-- 55°C
Weight	1kg
Size	200mm*118mm*44mm(L*W*H)

Wire:

