MA-CP - Manual Addressable Call Point with a highly visible LED alarm indicator which can be seen from afar. The manual call point has priority for a fast alarm response.


MA-CP is equipped with a short-circuit isolator.

System Functionality:

- Soft addressing automates the assigning of addresses with an automatic learning process controlled from the panel.
- · High visibility status LED.
- · Heavy duty terminals.
- · Single address.
- Optional removable cover which prevents unintended activation of the fire alarm.
- · Deactivation key.

Features & Benefits:

- · Quick and simple to install.
- · Easy maintenance.
- · Test key.
- Plug-and-play terminal connections for fast, resettable wiring.
- Two models available.
- · Indoor.
- · Weatherproof.





Technical Specifications:

Code	MA-CP	
Description	Addressable surface/flush mounting call point	
Standards	EN54-11, SII 1220 and TR TC EAC 043-2017	

Specification

Operating Voltage	17 - 32VDC	
Quiescent Current	<250µA	

Environmental

Environmental Operating Temperature	-10°C to +60°C	
Humidity (Non-Condensing)	0 - 93% RH	

Physical

Construction	PC/ABS		
Color	Red		
Weight	0.2 kg		
Ingress Protection	IP42		

Compatibility

Suitable For Use With	MTech MA Analog Addressable Fire Alarm Systems
-----------------------	---

Dimensions:

W. 87 mm | H. 87 mm | D. 57 mm (36mm flush)



Ord	er	Cod	6.
Old	CI	COU	

MA-CP (standard)

MA-CPWP (waterproof)